






Kinghelm®



SECTION A-A



RECOMMEND PCB LAYOUT(TOLERANCE=±0.05)

● Electrical Characteristics

When tested under the voltage of 24VDC and current of 25mA, it can be and plugged for 2000 times. Rated Current Not Often Switched by Circuit Changer: 100mA, Withstand Voltage 50VDC. Rated Current Often Switched by Circuit Changer: 25mA, Withstand Voltage 24VDC

Contact Resistance: Initial Value of 50mΩ Max

Insulation Impedance: 100m Ω, 500VDC Min

Dielectric Strength : 500VAC/1 minute

Interelectrode Capacitance: 5PF Max

Circuit: Single Contact With Single Selection

● Mechanical Properties

Operating force: 0.2kgf Max

Stroke of Push Button: 2.00mm

Operating Temperature: -20°C ~ +70°C

Storage Temperature: -40°C~+85°C

● FEATURES

Base: UL94V-0, PBT, Black

Upper Cover: UL94v-0,

PBT, Red, Black, Blue

Push Button: UL94V-0,

PBT, White

Terminal: Phosphor

Bronze

Dimension

Position	DIM.A(mm)
2	6.64
3	9.18
4	11.72
5	14.2
6	16.8
7	19.34
8	21.88
9	24.42
10	26.96
12	32.04

Dimensional Tolerance		Angle Tolerance		Projection		Product name	
X.	±0.60	X.	±5°	Unit	mm	EDS switching space 2.54mm	
.X	±0.38	.X	±3°	Paper size	A4	Product Series	Series KF1001
.XX	±0.25	.XX	±2°	SHENZHEN KINGHELM ELECTRONIC CO., LTD.			WWW.BDS666.COM
Drawing type		CUSTOMER		KH-BM2.54-1P			
Scale		1:1	Page 1/1				
Drawing Number		KF1001					
				0755-83044319			