


Kinghelm®



NOTES:


1. ELECTRICAL:

- 1.1. VOLTAGE RATING:DCV 300V 10MS
- 1.2. CONDUCTANCE RESISTANCE: 3.0 OHM/MAX.
- 1.3. INSULATION RESISTANCE: 5.0M OHM/MIN.
- 1.4. THE CABLE SHOULD BE 100% ELECTRICAL TEST
- 1.5. IT SHOULD BE NO ANY OPEN/SHORT,MISWIRING AND INTERMITTENT FAILURES.

2. MATERIAL:

- 2.1. SEE TABLE

3. ALL COMPONENTS ARE RoHS COMPLIANT.

NO.	PART	DESCRIPTION	QYT.			
			AS			
②	CONNECTOR	3rd Generation IPEX Connector	1			
①	Coaxial Cable	RF0.81 Black Coaxial Cable,OD:0.81mm	AS			
Shenzhen Kinghelm Electronics Co., Ltd		www.kinghelm.net				
KH-(RG0.81)-TX300-IPEX3-221						
ALL DIMENSION ARE IN MM	DRAWN	Jamy	DATE	2020-06-15		
	ENG.					
	COMPUTER GENERATED IN SOLIDWORKS	MFG.				
	DO NOT SCALE THIS DRAWING	Q.A.				
PROJECTION		GENERAL TOLERANCE FOR ANGLES X.X X.XX X.XXX ± 1° ± 0.3 ± 0.25 ± 0.150		SIZE	Number	REV
				B		A
				SCALE: Free	TYPE	SHEET 1 OF 1

CUSTOMER PIN: