




NOTES:

1. 0. ELECTRICAL CHARACTERISTIC:
1. 1. LOW LEVEL CONTACT RESISTANCE: INITIAL: 30m Ω MAXIMUM
FOR POWER AND GROUND CONTACTS.
INITIAL: 50m Ω MAXIMUM
FOR ALL OTHER CONTACTS.
APR: 10m Ω MAX 1 MIN CHANGE.
1. 2. DIELECTRIC WITHSTANDING VOLTAGE: 100V AC FOR ONE MINUTE AT SEA LEVEL.
2. 0. INSULATION RESISTANCE: 100M Ω MINIMUM.
2. 0. MECHANICAL CHARACTERISTIC:
2. 1. INSERTION FORCE: 35N (3.57kgf) MAXIMUM.
2. 2. EXTRACTION FORCE: INITIAL: 10N (1.02kgf) MINIMUM.
APR: 8N (0.816kgf) MINIMUM.



TOLERANCE UNSPECIFIED		Shenzhen Kinghelm Electronics Co., Ltd.			
TRANS H1:	0	±0.30	KH-2AF90WJ3.0-17.5J		www.kinghelm.net
	.00	±0.38			
	.00	±0.55			
	.000	±0.15	Dual-Layer USB 3.0 A/F, Half-Gold & Tin Plated		
	ANGLE	+3.00°			
CUSTOMER DRAWING					
		SIZE:A4	UNIT:mm	PART NO. USB-18X-XXXX	
CHECKED H1:		SCALE: 1:1	PROJECTION		REV.: B
APPROVED H1:		DWG. PATH			SHEET: 1/1